

# MASTER

CODICE	MODELLO	Ø TUBO	DIMENSIONI MAX LOCALE	VELOCITÀ	m³/h	POTENZA MAX ASSORBITA	ALIMENTAZIONE	dB(A) 1,5 mt
AP19981	ECOCOMFORT 160 RF	160 mm	50 mq *	bassa	28	2,0 W	230V~ 50Hz	27
				media	48	3,8 W		32
				alta	68	6,6 W		38
				sleep	15	nd		nd
AP19987	ECOCOMFORT 100 RF	100 mm	22 mq *	bassa	8	2,0 W	230V~ 50Hz	18
				media	18	3,8 W		23
				alta	30	6,6 W		28
				sleep	4	nd		nd
AP19980	ECOCOMFORT 160	160 mm	44 mq *	bassa	38	2,0 W	230V~ 50Hz	28
				alta	60	4,0 W		34
AP19984	ECOCOMFORT 100	100 mm	20 mq *	bassa	12	1,5 W	230V~ 50Hz	21
				alta	25	2 W		24

## UNITÀ VENTILANTI AGGIUNTIVE

AP19982	ECOCOMFORT SAT 160 RF	160 mm	50 mq *	bassa	28	2,0 W	230V~ 50Hz	27
				media	48	3,8 W		32
				alta	68	6,6 W		38
				sleep	15	nd		nd
AP19988	ECOCOMFORT SAT 100 RF	100 mm	22 mq *	bassa	8	2,0 W	230V~ 50Hz	18
				media	18	3,8 W		23
				alta	30	6,6 W		28
				sleep	4	nd		nd
AP19979	ECOCOMFORT SAT 160	160 mm	44 mq *	bassa	38	2,0 W	230V~ 50Hz	28
				alta	60	4,0 W		34
AP19985	ECOCOMFORT SAT 100	100 mm	20 mq *	bassa	12	1,5 W	230V~ 50Hz	21
				alta	25	2 W		24