

COD.	PESO IMPULSIVO K (l/imp)	DIMENSIONE NOMINALE DN	PORTATA NOMINALE Q _p	PORTATA MASSIMA Q _s	PORTATA MINIMA Q _i	CLASSE TEMPERATURA
ECC50WA	100	50 mm	15 m ³ /h	30 m ³ /h	0,6 m ³ /h	T130
ECC65WA	100	60 mm	25 m ³ /h	50 m ³ /h	1 m ³ /h	T130
ECC80WA	100	80 mm	40 m ³ /h	80 m ³ /h	1,6 m ³ /h	T130
ECC100WA	100	100 mm	60 m ³ /h	120 m ³ /h	2,4 m ³ /h	T130
ECC125WA *	100	125 mm	100 m ³ /h	200 m ³ /h	4 m ³ /h	T130
ECC150WA *	1000	150 mm	150 m ³ /h	300 m ³ /h	6 m ³ /h	T130
ECC200WA *	1000	200 mm	250 m ³ /h	500 m ³ /h	10 m ³ /h	T130
ECC250WA *	1000	250 mm	400 m ³ /h	1800 m ³ /h	40 m ³ /h	T130
ECC300WA *	1000	300 mm	600 m ³ /h	1200 m ³ /h	20 m ³ /h	T130