

COD.		PESO IMPULSIVO K (l/imp)	DIMENSIONE NOMINALE DN	PORTATA NOMINALE Q _p	PORTATA MASSIMA Q _s	PORTATA MINIMA Q _i	CLASSE TEMPERATURA
ECCF50W	*	100	50 mm	15 m ³ /h	30 m ³ /h	0,45 m ³ /h	T50
ECCF65W	*	100	60 mm	25 m ³ /h	50 m ³ /h	0,75 m ³ /h	T50
ECCF80W	*	100	80 mm	40 m ³ /h	80 m ³ /h	1,2 m ³ /h	T50
ECCF100W	*	100	100 mm	70 m ³ /h	120 m ³ /h	1,8 m ³ /h	T50
ECCF125W	*	100	125 mm	100 m ³ /h	200 m ³ /h	3 m ³ /h	T50
ECCF150W	*	1000	150 mm	150 m ³ /h	300 m ³ /h	4,5 m ³ /h	T50
ECCF200W	*	1000	200 mm	250 m ³ /h	500 m ³ /h	7,5 m ³ /h	T50
ECCF250W	*	1000	250 mm	400 m ³ /h	800 m ³ /h	12 m ³ /h	T50
ECCF300W	*	1000	300 mm	600 m ³ /h	1200 m ³ /h	18 m ³ /h	T50